

SMART/RG®

forward thinking

AnyWAN™ Gateways / SR905acv
FTTH/ETHERNET IAD + 5-Port Dual-Band 11ac WiFi

POWERED BY
SMART/OS™



THE SR905acv AnyWAN GATEWAY provides high performance and flexibility for broadband triple-play subscribers, effectively bridging the gap between copper and fiber.

Leveraging the latest Intel silicon solutions paired with SmartRG's industry-leading, open-source based SmartOS™ SDN/NFV-ready software platform, the SR905acv is the ultimate gateway for the connected home.

Blazing fast WiFi performance is delivered by a 802.11ac Wave 2 Dual-band Access Point, fully enabling delivery of triple play services over WiFi and delivering best-in-class speeds and reach within the home or place of business.

Pair the SR905acv with SmartRG's cloud-enabled Home Analytics™ and Device Manager™ for world-class customer experience delivery and comprehensive remote management.

/ HIGHLIGHTS

Speed to Burn and Room to Grow

With its quad-core Intel CPU and twin 802.11ac WiFi chipsets, each with 100% CPU Offload, the SR905acv has the power to manage whatever you throw at it without breaking a sweat, making it an excellent platform for the value-added applications Service Providers and their customers care about, like media-sharing, Parental Control, home-automation, and advanced analytics. Best-in-class WiFi throughput at high-client loads and small packet sizes delivers superior subscriber WiFi experiences even in the most challenging environments with high WiFi client counts in tomorrow's IoT-rich homes.

AnyWAN™

The SR905acv offers the ultimate in flexibility to Service Providers. The integrated SFP slot permits the use of any approved SFP module (e.g. GPON, Point-to-Point Active Ethernet) and the SR905acv is transformed into a Gigabit FTTH Gateway - no costly ONT needed!

/ FEATURES

- 5 Gigabit Ethernet ports
- Dual-band 802.11ac Wave 2 Access Point
 - 4x4 MU-MIMO @ 5GHz
 - 4x4 SU-MIMO @ 2.4GHz
- SFP slot for Gigabit FTTH broadband access
- Two USB 3.0 ports
- Two SIP-enabled FXS ports

/ BUILT-IN SUPPORT

- True, 1Gbps symmetric NAT throughput
- AnyClient™ beamforming to any 802.11 device
- Up to 64 clients per WiFi radio – best in class performance at scale
- Advanced WiFi Analytics and QoS
- Hardware Acceleration for true Gigabit performance
- K.21 Lightning protection

/ PRODUCT FEATURES

Interfaces

4 x 1000BASE-TX Gigabit LAN ports
1 x 1000BASE-TX Gigabit WAN port
1 x SFP WAN port
2 x RJ11 FXS ports (SIP)
2 x USB 3.0 ports

Wireless

802.11ac 5GHz 1.7Gbps Wi-Fi Access Point
• 4x4 MU-MIMO
802.11n 2.4GHz 800Mbps Wi-Fi Access Point
• 4x4 SU-MIMO
AnyClient™ beamforming for any 11a/b/g/n/ac device
Multiple SSIDs, including isolated Guest SSID
Wi-Fi QoS (WMM®) and WMM®- Power Save
Wi-Fi Protected Setup™ 2
WPA2, AES encryption
100% CPU Offload (Zero Wi-Fi processing on CPU)
DFS (Dynamic Frequency Selection)
802.11k/r/v for Whole-home WiFi roaming assist

Routing & Networking

RFC2516 PPPoE and PPPoE pass-through
RFC2684 Multiprotocol Encapsulation over ATM
RFC2364 PPPoA
802.1Q VLAN
DNS Proxy Server & Dynamic DNS client
DHCP Server and Client
DHCP Options 60 and 121
NAPT and NAT
IGMPv2/v3 Proxy and Snooping
LAN port to VLAN mapping
SmartQoS with Bufferbloat protection
USB Samba/DLNA/UPnP

Remote Management

SmartRG Home Analytics™
SmartRG Device Manager™
TR-069 with TR-181 Device Data Model
HTTP/HTTPS, SSH, and SNMP
Syslog logging (local/remote)
Real-time Status and Reporting
Remote/Live Updates
Configuration Backup and Restore
Custom Defaults & Themes

Security

Secure Boot, Encapsulated Core, ISEC Intel Security
Stateful Packet Inspection Firewall
Denial of Service attack prevention
Malware blackholing
TCP/IP/Port/interface filtering rules

VoIP

SIP/RTP/RTCP/SDP
Outbound Proxy
Fax/modem passthrough & ITU-T T.38 Fax Relay
RFC2833 DTMF tone detection/generation
ITU-T G.168 Echo Cancellation
Silence Suppression (VAD-DTX-CNG)
G.711 μ -law and A-law codecs

/ SPECIFICATIONS AND STANDARDS

Mechanical

Dimensions: 259mm*206mm*54mm (W*H*D)
Weight: 550g

Electrical

AC power adapter: 100 to 240VAC @ 50/60Hz
DC voltage: 12V, 3A

Safety & Certifications

FCC Part 15, Subpart B and ICES-003 for Class B
FCC Part 15, Subparts C & E and ISED RSS-247 for RF
FCC Part 68 and ISED CS-03 registered
UL 60950-1 (Bureau Veritas listed)
Overvoltage/Overcurrent: K.21 compliant

Environmental

Meets or exceeds Telcordia GR-63-CORE for:

Temperature:

- 0° to 45°C (Standard Operating)
- -40° to 70°C (Non-operating)

Humidity:

- 5% to 90% (Non-condensing, Standard Operating)
- 5% to 95% (Non-condensing, Non-operating)

501 SE Columbia Shores Boulevard, Suite 500
Vancouver, Washington, 98661 USA
+360 859 1780 / smartrg.com

© 2019 SmartRG, Inc. SmartRG and the SmartRG logo are registered trademarks or trademarks of SmartRG, Inc., incorporated in the U.S.A. All other names are properties of their respective owners. Product photo may differ from actual product; however, functionality remains as stated above. Specifications are subject to change without notice. D5SR905ACV0802